


**A** Precision 1 1/4" Nom. Swage Press for the production of hose assemblies of all types. Designed specifically for operators on the move, it has a versatile, lightweight/compact design. Incorporating a special "Fast Approach" feature means less pumping operations are required to swage a hose. Manufactured from steels with high alloying components subjected to new surface treatments will provide the owner many years of trouble free operation.



**SOUTHCOTT PTY LTD**  
 A.B.N. 27 007 870 662  
 243 HALIFAX ST,  
 ADELAIDE S.A. 5000

PH. 61 - 8 - 8228 2411  
 FAX. 61 - 8 - 8223 3413

**AVAILABLE 4th QUARTER 2001**



### Features:

- 1 1/4" 4 Wire / Hydraulic hose capability.
- Lightweight design designed for mobile use.
- Cost effective design.
- Swaging accuracy 0.05mm.
- Special "Fast Approach" feature.
- **COLOUR SWAGE**
- Standard swaging range 16 to 55mm diam.  
Extended swaging range 7 to 60mm diam.
- High performance gas struts for fast return.

### Specifications:

#### Dynamic:


Nom. Size (Hydraulic Hose Size Inches).....	1
Die Set Size (mm nom.).....	32E-XX
Swaging Range (mm with Std. Die Set).....	16 to 55
(mm with Optional Dies).....	7 to 60
Max. Die Set Opening (mm + Die Set Size).....	30
Radial Swaging Force (kN).....	1500
Pumps for full cycle.....	30

#### Physical:

Dimensions (Plan mm x mm x Height mm).....	300 x 300 x 200
Weight (Without Dies & Oil kg).....	20
Shipping Space (m x m x m).....	0.030
Shipping Weight (kg).....	25
Crate Size (Plan m x m x Height m).....	0.35 x 0.35 x 0.35
Rated Pressure (bar).....	690
Pump Flowrate (cc/stroke).....	11.26 + 2.47
Reservoir Capacity (litres).....	0.901
Filtration (um).....	100

### Installation:

#### OPTIONS:



**CS32ESDS**  
Standard Die Set



**CS32EQCT**  
Quick Change Tool