


A Precision 1 1/4" Nom. Swage Press for the production of hose assemblies of all types. Designed specifically for operation with an air supply, it is versatile, lightweight and compact. Incorporating a special "Fast Approach" feature means less pumping operations are required to swage a hose. Manufactured from steels with high alloying components subjected to new surface treatments will provide the owner many years of trouble free operation.



SOUTHCOTT PTY LTD
 A.B.N. 27 007 870 662
 243 HALIFAX ST,
 ADELAIDE S.A. 5000

PH. 61 - 8 - 8228 2411
 FAX. 61 - 8 - 8223 3413

AVAILABLE 4th QUARTER 2001



Features:

- 1 1/4" 4 Wire Hydraulic hose capability.
- Economical solution due to air driven supply.
- Cost effective design.
- Swaging accuracy 0.05mm.
- Special "Fast Approach" feature.
- **COLOUR SWAGE**
- Standard swaging range 16 to 45mm diam.
Extended swaging range 7 to 45mm diam.
- High performance gas struts for fast return.

Specifications:

Dynamic:

Nom. Size (Hydraulic Hose Size Inches).....1 1/4"
 Die Set Size (mm nom.).....32E-XX
 Swaging Range (mm with Std. Die Set).....16 to 55
 (mm with Optional Dies).....7 to 60
 Max. Die Set Opening (mm + Die Set Size).....30
 Radial Swaging Force @ 700 kPa air supply (kN).....1500
 Time for full cycle @ 700 kPa air supply (sec).....30

Physical:

Dimensions (Plan mm x mm x Height mm).....
300 x 300 x 200
 Weight (Without Dies & Oil kg).....20
 Shipping Space (m x m x m).....0.030
 Shipping Weight (kg).....25
 Crate Size (Plan m x m x Height m).....0.35 x 0.35 x 0.35

Hydraulic:

Rated Pressure (bar).....690
 Pump Flowrate (cc/stroke).....0.8
 Reservoir Capacity (litres).....2
 Filtration (um).....100

Installation:

OPTIONS:



CS32ESDS
Standard Die Set



CS32EQCT
Quick Change Tool