


A Precision 2" Nom. Swage Press for the production of hose assemblies of all types. Versatile lightweight / compact design. Manufactured from steels with high alloying components subjected to new surface treatments will provide the owner many years of trouble free operation.

Features:

- 2" 4 Wire Hydraulic hose capability.
- Two speed design for rapid approach and retract times with large clearance.
- COLOUR SWAGE
- Swaging accuracy 0.05mm.
- SIEMENS control electrics.
- Special "Anti-Pinch" die design.
- Standard swaging range 16 to 77mm diam. Extended swaging range 7 to 85mm diam.
- Auto motor control with soft start.
- UL and CE approvals



SOUTHCOTT PTY LTD
 A.B.N. 27 007 870 662
 243 HALIFAX ST,
 ADELAIDE S.A. 5000

PH. 61 - 8 - 8228 2411
 FAX. 61 - 8 - 8223 3413



Specifications:

Dynamic:

Nom. Size (Hydraulic Hose Size Inches).....	2
Die Set Size (mm nom.).....	50E-XX
Swaging Range (mm with Std. Die Set).....	16 to 77
(mm with Optional Dies).....	7 to 85
Max. Die Set Opening (mm + Die Set Size).....	40
Radial Swaging Force (kN).....	2500
Cycle Speed (Full Stroke-Complete Cycle sec.).....	18

Physical:

Dimensions (Plan mm x mm x Height mm).....	600 x 420 x 570
Weight (Without Dies & Oil kg).....	130
Shipping Space (m x m x m).....	0.144
Shipping Weight (kg).....	160
Crate Size (Plan m x m x Height m).....	0.72 x 0.55 x 0.78

Electrical:

Supply (Volts / Amps).....	110 / 220 VAC / 22 - 11
Phase (No.).....	1
Power (kW).....	1.8
Electric Motor Speed (RPM @ 50 Hz).....	2880
Control Power (Volts).....	24 VDC

Hydraulic:

Rated Pressure (bar).....	300
Pump Flowrate (l/min).....	4.6
Reservoir Capacity (litres).....	10
Filtration (um).....	100

OPTIONS:



CSFP
Foot Pedal Control



CS50EQCT
Quick Change Tool



CS50EQCS
Quick Change Stand



CS50EQCR
Quick Change Rack



CS50ESDS
Standard Die Set