


A Precision 2" Nom. Swage Press for the production of hose assemblies of all types. Designed specifically for operators on the move, it has a versatile, lightweight/compact design. Incorporating a special "Fast Approach" feature means less pumping operations are required to swage a hose. Manufactured from steels with high alloying components subjected to new surface treatments will provide the owner many years of trouble free operation.



SOUTHCOTT PTY LTD
 A.B.N. 27 007 870 662
 243 HALIFAX ST,
 ADELAIDE S.A. 5000

PH. 61 - 8 - 8228 2411
 FAX. 61 - 8 - 8223 3413

AVAILABLE 2nd QUARTER 2002

- 2" 4 Wire / Hydraulic hose capability.
- Lightweight design designed for mobile use.
- Cost effective design.
- Swaging accuracy 0.05mm.
- Special "Fast Approach" feature.
- **COLOUR SWAGE**
- Standard swaging range 16 to 77mm diam.
Extended swaging range 7 to 85mm diam.
- High performance gas struts for fast return.



Specifications:

Dynamic:

Nom. Size (Hydraulic Hose Size Inches).....2"
 Die Set Size (mm nom.).....50E-XX
 Swaging Range (mm with Std. Die Set).....16 to 77
 (mm with Optional Dies).....7 to 85
 Max. Die Set Opening (mm + Die Set Size).....40
 Radial Swaging Force @ 700 kPa air supply (kN).....2500
 Time for full cycle @ 700 kPa air supply (sec).....30

Physical:

Dimensions (Plan mm x mm x Height mm).....
300 x 300 x 200
 Weight (Without Dies & Oil kg).....20
 Shipping Space (m x m x m).....0.030
 Shipping Weight (kg).....55
 Crate Size (Plan m x m x Height m).....0.35 x 0.35 x 0.35

Hydraulic:

Rated Pressure (bar).....690
 Pump Flowrate (cc/stroke).....0.8
 Reservoir Capacity (litres).....2
 Filtration (um).....100

Installation:

OPTIONS:



CS50ESDS
Standard Die Set



CS50EQCT
Quick Change Tool